



SUPER CONCENTRATED **POLYMER**

Product Information

Category: Additive

3 & 5 gallon bucket

1500 Series

Description and Use:

A super concentrated acrylic modifier used to greatly increase strength and adhesion when used as an additive to the mixture in conjunction with Granicrete Texture and Base Blend. Used throughout the process of Granicrete's Floor Overlay and Micro-Topping Systems.

A mixture of 2 parts water and 1 part Super Concentrated Polymer can be used to prime a porous un-sealed surface before using Granicrete's Alternative Flooring System. This primer will help prevent out-gassing and discoloration when applying Base and Texture Blends. Base and Texture blend must be applied to the surface within 4 hours of applying the primer.

Super Concentrated Polymer is also used to create an antique colorant. 1 gallon of water mixed with 24oz of Polymer and 6-10 caps of a Dispersion Colorant.

During the application of Powdered Accents a mixture of 2 parts water and 1 part Polymer is used to help adhere the Powdered Accents to the surface.

This engineered product used in the following Granicrete Systems:

- | | |
|---|---|
| <input checked="" type="checkbox"/> Floor Overlay / Micro-Topping | <input checked="" type="checkbox"/> 3D |
| <input checked="" type="checkbox"/> Interior | <input type="checkbox"/> Epoxy Flooring |
| <input checked="" type="checkbox"/> Exterior | <input checked="" type="checkbox"/> Shower FX |
| <input type="checkbox"/> Countertop | <input checked="" type="checkbox"/> Outdoor Islands |

Its significant characteristics include:

- ✓ Not pre-cut with water (maintains strength)
- ✓ Multi-uses throughout the Flooring System
- ✓ Helps cure flooring blends to almost 6000 psi

Coverage:

3-gallon pail – 6 bags of Base or Texture Blend

5-gallon pail – 10 Bags of Base or Texture Blend

Always allow for extra Polymer as it is used in many different applications.

Color:

White

Mixing:

A light mix with paint stick or shake the bucket before opening is recommended before use.

Application:

Base & Texture Blend Mixture: 4-5 quarts of water, 2 quarts of Super Concentrated Polymer, 50lb bag of Base or Texture Blend

Antique Colorant: 1 gallon of water, 24oz of Polymer, 6-10 caps of a Dispersion

Primer or Powdered Accent Liquid: 2 parts water, 1 part Polymer for dipping sponge to then grab Powdered Accent.

Clean Up:

Equipment should be cleaned with environmentally safe solvent immediately after use

Wear Personal Protective Equipment
Read SDS before using this product.
DOT/Flash Point – Non-flammable Liquid Classification, not regulated.

Manufacturer/Distributor Warranty: As neither the manufacturer nor the distributor has control over the actual installation of this product, the manufacturer and distributor disclaim any and all warranties expressed or implied regarding color shade, appearance, and product performance at and after opening product containers. Manufacturer and distributor recommendations and suggestions are made without guarantee. Conditions of installer's and consumer's use of this product are beyond the control of manufacturer and distributor. Manufacturer and distributor disclaim any liability incurred in connection with the use of this product or information contained herein.