



## **GRANICRETE SRA**

### **(Slip Resistant Additive)**

**Product Code 7200**

#### **Description:**

Granicrete SRA is a non-polluting, long-lasting and recyclable plastic engineered to bite into the top coat and provide slip resistance.

#### **Uses:**

SRA is used to help reduce slipperiness of tightly troweled surfaces or coated surfaces.

#### **Advantages:**

- Safe for Substrates, Primers,
- Fast; Easy-To-Use
- Non-toxic; Environmentally Safe
- No Chemical Solvents
- Consistent Specific Gravity
- Long-lasting

#### **Typical Coverage:**

For Epoxy Coatings: 6-8 fluid oz. / gallon

For Floor Sealers: 4-6 fluid oz. / gallon

#### **Packaging:**

32 fluid oz. container with options of Small 40-60 mesh grit or Coarse 20/40 mesh grit granules depending on slip resistant need and cosmetic acceptance of the consumer.

#### **Application:**

Mix thoroughly into your final coat at the coverage ratio above and roll out thoroughly across the floor to the desired mix ratio. Be sure to monitor continued mixing of SRA throughout the sealing process.

Can also be scatter tossed broadcast into wet sealer coat followed by a final sealer coat to encapsulate the SRA is more desirable.

**Technical Data:**

MOH Hardness	3	
ASTM D638	Elongation	<1%
ASTM D638	Tensile Strength	5,000-6000 psi
ASTM D695	Compressive Strength	22,500 psi
Meets MIL Spec MIL-P-85891A		

This product is for use by Granicrete Independent applicators only.

Wear Personal Protective Equipment.

Read SDS before using this product.

DOT/Flash Point – Non-flammable Liquid Classification. Not regulated.

Granicrete International, Inc.

866-438-9464

[www.Granicrete.com](http://www.Granicrete.com)

**Manufacturer/Distributor Warranty:** As neither the manufacturer nor the distributor has control over the actual installation of this product, the manufacturer and distributor disclaim any and all warranties expressed or implied regarding color shade, appearance, and product performance at and after opening product containers. Manufacturer and distributor recommendations and suggestions are made without guarantee. Conditions of installer's and consumer's use of this product are beyond the control of manufacturer and distributor. Manufacturer and distributor disclaim any liability incurred in connection with the use of this product or information contained herein.