



COUNTERTOP BLEND

Product Information

Category: Texture

40lb pail / 18.14kg

Description and Use:

This engineered product used in the following Granicrete Systems:

- | | |
|----------------------------------------------------|-----------------------------------------------------|
| <input checked="" type="checkbox"/> Floor Overlays | <input checked="" type="checkbox"/> 3D |
| <input checked="" type="checkbox"/> Interior | <input type="checkbox"/> Epoxy Flooring |
| <input checked="" type="checkbox"/> Exterior | <input checked="" type="checkbox"/> Shower FX |
| <input checked="" type="checkbox"/> Countertop | <input checked="" type="checkbox"/> Outdoor Islands |

Its significant characteristics include:

- ✓ Excellent adhesion to existing countertop surfaces for “resurfacing” purposes
- ✓ Excellent adhesion for MDF and MDX for new installation purposes
- ✓ Wipe-Away technology permitting the installer to literally “wipe away” topical colors within 30-45 minutes of application to easily start desired coloring over again
- ✓ This proprietary formulation provides for optimal color enhancement of topical coloring to yield the exceptionally authentic looks for granite, marble, and other stone effects
- ✓ Excellent for brush coating over prepared tile surfaces as a primer coat for Floor Overlay and Micro-Topping systems.

Coverage:

Coverage for a 40lb pail is approximately 60 square feet (1/6 inch) inclusive of 4 coats and edging coat per use under the Granicrete Original Countertop Surfacing System.

Surface Preparation:

For best results, the surface to be covered must be dry and free of dust, wax, grease, oil or any other surface contaminate.

Measuring:

Using the prescribed ration of Granicrete Countertop Blend to water as instructed in the Original Countertop Surfacing System manual produces best results.

Mixing Tools:

Container – Should have smooth flat bottom and be clean and dust free.

Paddle – Must use drill and paddle mixer assuring until texture is thoroughly mixed having no clumps. Period mixing is recommended to maintain texture consistency throughout installation.

Mixing and Application:

Certified Installers must reference Granicrete’s Countertop Training Manuals per the individual stages required.

Drying Time:

Drying time is enhanced with warmer ambient temperature and moving air. Do not apply direct heat to the surface.

Clean Up:

Clean up Granicrete Countertop Blend should be done while it is in its liquid state. After it has been cured, it can be removed by mechanical grinding. Therefore, it is advisable to clean your tools immediately after use.

Technical Data:

COMPRESSIVE STRENGTH: ASTM C109

@ 24 hours	950 psi
@ 7 days	3,120 psi
@ 28 days	4,150 psi

FLEXURAL STRENGTH: ASTM C78

@ 24 hours	350 psi
@ 7 days	1,090 psi
@ 28 days	1,410 psi

*Independent laboratory tests were conducted
and certified by
Western Technologies, Inc.
"The Quality People Since 1955"*

Wear Personal Protective Equipment
Read SDS before using this product
DOT/Flash Point – Non-flammable Liquid Classification, not regulated

Manufacturer/Distributor Warranty: As neither the manufacturer nor the distributor has control over the actual installation of this product, the manufacturer and distributor disclaim any and all warranties expressed or implied regarding color shade, appearance, and product performance at and after opening product containers. Manufacturer and distributor recommendations and suggestions are made without guarantee. Conditions of installer's and consumer's use of this product are beyond the control of manufacturer and distributor. Manufacturer and distributor disclaim any liability incurred in connection with the use of this product or information contained herein.