



GRANICRETE
INTERNATIONAL

Coastal Fog

For this finish you will need:

1. Black FX
2. Burgundy-Dispersion
3. Ponderosa Green – Acryli-Shade
4. Groutline Grey-Dispersion
5. Burntwood Black – Acryli-Shade
6. Taupe-Dispersion



Mixing Procedure:

1. Mix Black FX (2 caps to 24oz of water) into a *Granicrete* professional spray bottle.
2. Mix Burgundy (3 caps to 24oz of water) into a *Granicrete* professional spray bottle.
3. Mix Ponderosa Green (4oz to 24oz of water) into a *Granicrete* professional spray bottle.
4. Mix Groutline Grey (2 caps to 24oz of water) into a *Granicrete* professional spray bottle.
5. Mix Burntwood Black (4 caps to 24oz of water) into a *Granicrete* professional spray bottle.
6. Mix Taupe (2 caps to 24oz of water) into a *Granicrete* professional spray bottle.

Step-by-Step Procedure:

1. Apply all Granicrete Countertop Blend coats per installation instructions.
2. Mist and speckle 75% of the surface using Black FX. While still wet, proceed.
3. Mist and speckle 40% of the surface using Burgundy. While still wet, proceed.
4. Mist and speckle 20% of the surface using Ponderosa Green. Allow to dry before proceeding.
5. Using sponge to rub color in, mist and spot flood 40% of the surface using Groutline Grey. While still wet, proceed.
6. Mist and speckle 50% of the surface using Burntwood Black. While still wet, proceed.
7. Mist and speckle 30% of the surface using Taupe.
8. Allow surface to completely dry and then apply Granicrete Crystal Top Epoxy per product instructions.

Professional Tip: Constantly shake up FX colors while being used in a spray bottle. The powder within each FX color is what makes them unique. If the color rest in the spray bottle the powder will settle to the bottom.

Coastal Fog Notes:

