



POLY LOW ODOR

Product Information

Category: Sealer

16 oz, 1 & 5 Gal Pail

Available in Gloss

Description and Use:

This self-crosslinking water based sealer provides chemical resistance and great hot tire resistance with two options for the desired shine. The Poly Low Odor provides an alternative to quick dry solvent based sealers. This sealer will not soften in extreme heat like solvent based acrylic sealers. Poly Low Odor is a great choice for interior and exterior applications. Granicrete Floor Overlay and Micro-Topping, colored concrete, plain concrete, pavers, bricks and other porous surfaces are suitable to be sealed with Poly Low Odor.

Gloss provides a wet look with the same great chemical resistance and hot tire resistance.

This engineered product used in the following Granicrete Systems:

- | | |
|---|---|
| <input checked="" type="checkbox"/> Floor Overlays / Micro-Toppings | <input checked="" type="checkbox"/> 3D |
| <input checked="" type="checkbox"/> Interior | <input type="checkbox"/> Epoxy Flooring |
| <input checked="" type="checkbox"/> Exterior | <input type="checkbox"/> Shower FX |
| <input type="checkbox"/> Countertop ("Concrete Look" Primer) | <input checked="" type="checkbox"/> Outdoor Islands |

Its significant characteristics include:

- ✓ Low odor allows for interior use
- ✓ Does not soften in extreme heat like solvent based sealers
- ✓ Non-Yellowing
- ✓ Excellent hot tire resistance
- ✓ Low V.O.C. (meets all Southern California A.Q.M.D. requirements)

Coverage:

2 coats are recommended for this product as a final sealer but highly recommended for a primer coat for WB-P53 for interior floors. 200 square feet per gallon for combined two coats and up to 400 square feet for one coat.

Colors:

Clear with Gloss providing a "wet look".

Pre-Inspection:

Surfaces must be completely dry, clean and free of debris.

Surface Preparation:

As a sealer over concrete – When applying directly over concrete as a clear sealer, the surface may be lightly abraded. Make sure no contaminants or prior sealers are present. Roll thin and do not allow to puddle.

As a sealer over Granicrete's decorative concrete – Make sure no contaminants or prior sealers are present. Make sure to properly neutralize and clean floor if acid stained before.

Mixing and Application:

Not normally needed. Lightly stirring can be helpful if product has been in storage more than a couple months.

Sealer should be applied by 3/8-1/2" nap shed resistant roller. Sealer may be applied with pump bug sprayer if the sealer is back-rolled to help reduce puddling.

When rolling, be sure to be smooth and consistent. Rolling to quickly will cause sealer to bubble and puddle.

Avoid over rolling, as product can be applied to thin. The desired thickness for your first coat is just before the sealer starts to puddle.

2nd Coat Application – Apply directly over prior coat as soon as prior coat is dry which is typically within an hour.

For reseat – Prior seal must be a water based sealer. Pressure wash the surface and allow to dry. Once the surface is dry, follow application technique listed above. Always test a small area and observe before proceeding. Apply two coats as recommended if used as a final sealer.

Maintenance:

Cleaning is best done by mopping surface with mild soap and water or mild detergent. For best appearance, reseal the surface every 1-3 years.

Limitations:

- ✓ Concrete surface should be above 55°F during application and drying time
- ✓ Do not allow to puddle or run on vertical surfaces
- ✓ Do not apply over damp surfaces
- ✓ Do not apply over solvent based sealers
- ✓ Do not use on wood surfaces
- ✓ Do not use on areas vulnerable to solvent attack
- ✓ Please read SDS sheet before use (available online)

Clean Up:

Equipment should be cleaned with environmentally safe solvent immediately after use.

Wear Personal Protective Equipment
Read SDS before using this product
DOT/Flash Point – Non-flammable Liquid Classification, not regulated

Manufacturer/Distributor Warranty: As neither the manufacturer nor the distributor has control over the actual installation of this product, the manufacturer and distributor disclaim any and all warranties expressed or implied regarding color shade, appearance, and product performance at and after opening product containers. Manufacturer and distributor recommendations and suggestions are made without guarantee. Conditions of installer's and consumer's use of this product are beyond the control of manufacturer and distributor. Manufacturer and distributor disclaim any liability incurred in connection with the use of this product or information contained herein.